SPECIFICATIONS

G9F-4
G9F-6

Professional Freestanding Oven Range

A synthesis of European design, ergonomics, and professional performance, the Kleenmaid Professional range of freestanding ovens offers freedom of choice with a range of made to order colour and cooktop options. The Kleenmaid professional range offers a variety of cooking capacities and multifunction programs to suit everyone from the largest family to the greatest entertainers. With custom design options, the Kleenmaid professional freestanding oven spoils even the most demanding chefs.

Features

Oven Capacity:	96 litres
Programs:	9 multi-function programs - including rotisserie
Colour options:	11 made to order colour options
Cooktop options:	7 cooktop options
Dimensions:	899mm (W) x 900 - 970*mm (H) x 623mm (D)
	*Cooker is 900mm high + feet adjustment 20mm. There is an optional cooker support accessory for purchase which adds another possible 50mm to the height.
Accessories:	SA-SZ9 cooker support & plinth
(optional)	TSR03 telescopic guides
	SK90 stainless steel splashback
	K90 professional rangehood

10

10 Year Warranty*

For your nearest store call 13 13 08
www.kleenmaid.com.au

Kleenmaid PROFESSIONAL

SPECIFICATIONS

Professional Freestanding Oven Range





INSTALLATION

Ovens may be installed within the cupboard surrounds or at the end of the bench run.Non combustible material should be located behind the appliance when fitting. Required clearances around the gas cooktops (according to model) as per AS5601 - AG601 Gas Regulation (see Use and Care manual).

Height of Cooktop to Benchtop

Where the distance from the edge of any burner to a horizontal surface is **less than 200mm (*)** the surface must be either : 10mm (min) below the level of the hob, or have the vertical component of the surface suitably covered with a non-combustible material as specified in AS4501 (AG601). **ie. If less than 200mm (*)** the cooktop can only be level with the benchtop if the benchtop is of non-combustible material. Ensure your flex/pipe (gas connection) and cable (electrical connection) are not constricted or crushed. Make sure the gas connection fittings are easily accessible.


G9F-4T


G9F-4B


G9F-4F


G9F-6V


G9F-6


G9F-4C


G9F-4G

IMPORTANT NOTE ON HEIGHTS: 900 - 970mm
Cooker is 900mm high + feet adjustment 20mm.
There is an optional cooker support accessory for purchase which adds another possible 50mm to the height.

AGA Gas Approval No. 6404; Electrical Approval No. Q03102

Model	Capacity (Litres)	Gas Rating kW	Gas Rating MJ	Dimensions Width(mm)	Dimensions Height(mm)	Dimensions Depth (mm)	Electrical Rating Voltage	Electrical Rating kW	Electrical Rating Amp
G9F-6	96	11.95	44	899	900 - 970	599	240	2.9	14
G9F-4T	96	9.05	33	899	900 - 970	599	240	5.3	24
G9F-4B	96	9.05	33	899	900 - 970	599	240	5.3	24
G9F-4F	96	9.05	33	899	900 - 970	599	240	5.1	23
G9F-4G	96	9.05	33	899	900 - 970	599	240	5.4	24
G9F-4C	96	9.05	33	899	900 - 970	599	240	5.3	24
G9F-6V	96	NA	NA	899	900 - 970	599	240	12.7	53

*Technical Specifications and product sizes can be varied by Manufacturer without notice. Any cut-outs for appliances should only be by physical measurements. Drawings are not to scale. All information supplied is for general reference purposes only and is on the understanding that Kleenmaid Pty Ltd will not be liable for any loss, liability or damage whatsoever arising as a result of reliance of such information.